

EW20 Weighing Indicators



T-Scale



Features

4.3-inch color display with graphic interface
The Maximum storage 999 PLU, which can be quickly called by scanning
Support multi-language
Multi-user permission management
Standard RJ45 network communication, data can be uploaded/sent via Ethernet
Standard USB storage, you can import/export data via U disk
Standard RS232 interface can be connected to PC or printer

Background management software: with product management, customized print format, Report management, online update and other functions


Technical Data

Display: 4.3 inch color LCD display, resolution 480x 272 px
Power: AC adapter (100~240VAC/12V2500mA), rechargeable (lithium battery 7.4V/5200mAh).
Memory: 999 PLU and 30,000 weighing data
Operation temperature: -10 °C/40 °C
Interface: RS232x1, USB2.0 x1, RJ45x1, Loadcellx1
Keyboard: 33 membrane keys
Built-in Printer: 58mm, Support label and receipt combined printing


Accessories

- RS485 communication serial port
- Bluetooth 5.0 can transfer data to PC or Bluetooth-configured device
- Analog output (0~10V or 4~20mA optional)
- Dual scales interface
- Label printer
- Ticket printer
- 3 color light tower
- Scanner


Standard



Factory



Option



Model	EW20
Housing	ABS plastic
Dimensions	304×205×145mm
Net weight	2kg
nmax.	7500 for approved, 30000 for none approved
Load cell input resistance	43~1600 ohms
Load cell excitation voltage	5VDC
Vmin(only for approval)	0.5uV
Cable length	461m/mm ²
Load cell connector	7 pin connector

* Specification to change without notice